



# Ampliroll®

# 13,000 POUNDS

## AL 90 SERIES



### Why buy a HookLift?

Do you have trucks that are not always being used?  
Do you have a difficult time finding quality drivers?  
Is there a piece of equipment you could use, but  
can't justify adding another truck?

**It's Multi-tasking for your truck.  
The possibilities are Infinite.**

With an Ampliroll® you can do just about anything.

**Deliver — Load — Dump**



### FEATURES

- **Sliding Jib** gives you greater range of body lengths and optimal weight distribution.
- **Twin Pivot** allows you to dump a uniform pile of material.
- **Dual Cylinders** gives greater stability while dumping and loading.
- **Safely** operated from the drivers seat.
- **Dock Level** loading and unloading.
- **Double** your payload by pulling another body on a trailer.
- **Maneuverable** to operate, the container can be loaded within a **60 degree** arc.
- **Spot** the container exactly where you want it, by pushing it into place with no damage.
- **Quickly** loads a body in less than one minute.
- **Investment** that will outlast your truck, Amplirolls® will last over **25 years**.
- Meets all highway safety standards.



The Ampliroll® HookLift was invented in 1969. Our process of laser cutting and robotic welding enables us to provide you with a complete line of hooklifts, that eliminate the use of **SHIMS** and **WEAR PADS**.

***Ampliroll® has been imitated  
but never duplicated.***

***Compare the difference before you buy.***



Ampliroll® Model	AL 90S-12	AL 90L-14
<b>Lifting Capacity</b> (including container)	13,000 lbs	13,000 lbs
<b>Shipping Weight</b>	1790 lbs.	1790 lbs.
<b>Dump Angle</b>	58 degrees	61 degrees
<b>Cab to Axle</b>	84 to 108 inches	108 to 126 inches
<b>Over-All Length</b>	126 inches	144 inches
<b>Body Length</b>	8 to 13.5 feet	9 to 15 feet
<b>Hydraulic Specifications:</b>		
Pump - Axial piston, 5,700 psi, 7 GPM @ 1,200 RPM, SAE B, direct mount		
Controls - Electric in cab		
Reservoir - 4 gallons		
Filter - 10 micron, return line with replaceable cartridge		
Maximum operating pressure - 5,000 psi		
Hoses, tubes & fittings all JIC/SAE specifications		
<b>Steel: Special Alloy</b>	ASTM A 514 in jib, central arm and tilting frame ASTM A 572 grade 60 type 2 subframe	
<b>Safety Devices:</b>	Counter-balance valve to hold cylinder if hose breaks. Hoist automatically locks into dump mode when container is locked into holdowns.	
<b>Truck Requirements:</b>	GVWR - 15,000 to 20,000 lbs	

**Notice:** Longer containers may not comply with I.C.C. bumper regulations and can effect dump angle.

Inside Controls



Distributed by:



**marrel**  
CORPORATION

4750 14 Mile Road NE  
Rockford, MI 49341  
Phone: (616) 863-9155  
Fax: (616) 863-9177  
Toll Free: (866) 822-3580  
E-mail: [ampliroll@amplirollusa.com](mailto:ampliroll@amplirollusa.com)  
[www.amplirollusa.com](http://www.amplirollusa.com)