

© Ranger Automated Side Loader

Ease of operation and superior design are what set the Ranger ASL apart from all other automated side loaders.

Standard Wide Body design with roof mount tailgate cylinders offers more volume with the same body length.

The Bridgeport Automated Arm is the most efficient arm in the industry. It is body mounted for stability and durability. With fewer moving parts, maintenance is a breeze.

The Ranger also features a folding hopper door that allows a lower pitch-in height and easier cart removal.

The hopper features water-tight clean out doors that are easily reached from ground level.

EFFICIENT

- Automatic Pack Cycle
- One Piece Packer/Follower
- Tapered Body for Easier Discharge
- Self -Locking Tailgate w/ Watertight Seal

• Electric Over Hydraulic Controls

- Positive Stop Piston Pump Means No Oil Flows Until Controls Are Activated
- 96" Reach Body Mounted, Lever Action Arm
- Universal Cart Grips 30 to 450 gal

ELIABLE



Toll Free: 800.559.8520 Office: 254.559.2533

email: sales@bridgeportmfg.com

1000 Industrial Pkwy Breckenridge, TX 76424 www.bridgeportmfg.com





Ask about the Off Road Ranger package available to suit your individual needs. Features:

- 1. Extended Arm Elevator
- 2. Extended ICC Bumper
- 3. Extended steps on chassis door

All Models May Be Modified Per Customer Requirements



Body Specifications	
Body Capacity	27 yd ³ - 29 yd ³ - 31 yd ³ - 33 yd ³ - 35 yd ³ - 37 yd ³
Body Styles	Hoist to Dump or Full Eject
Floor	3/16" AR Plate w/ 1/4" Overlay at Hopper
Sides	10 ga Hi-Ten Tapered For Easy Dumping
Roof	10 ga Hi-Ten - Tapered Front to Back
Tailgate	1 Piece 10 ga - Positive Locking w/ Rubber Seal

Packer / Hopper Specifications		
Packer	1 Piece Packer/Follower w/ Slide-in Wear Strips	
Hopper Capacity	4 yd³	
Hopper Floor	3/8" Hardox 450 Plate	
Hopper Clean Out	Trough w/ 2 Rubber Sealed Clean Out Doors	
Hopper Door	Fold Down Door for Hand Loading - 78" Pitch-in	

Automated Arm Specifications		
Reach	96" or Optional 144" Extended Reach	
Cycle Time	7-8 Seconds @ 750 RPM	
Lift Capacity	1000 lbs (approx.)	
Grips	Universal (30-450 gal) carts	
Arm Carriage	Twin Rail For Super Stability	
Controls	Electric over Hydraulic Joystick & Rocker Switches	

Hydraulics	/ Bore x Stroke
Tailgate Cylinders	(2) 3" x 18" / TG Lock Cyl- (2) 3" x 4"
Packer Cylinders	(2) 4-1/2" x 46" / Full Eject Cyl- (1) 6-1/2" x 203"
Arm Cylinders	Lift- 2" x 12" / Grip- 2" x 28" / Dump- 3" x 20" / Reach- 2" x 72"
Hoist Cylinders	(2) 5-1/2" x 72" 3-Stage telescoping mounted outside frame
Pump / Valves	Piston Pump with Cartridge Valves

Options - Contact your local dealer for a full list of options		
Multiple CNG Configurations	Extended Reach Arm	
Frame Mounted Tool Box	Extended Warranty	



Contact your local dealer: