


www.obrienmfg.com toll-free phone: 800-638-1901



The Big Machine at Home or the Office

For the toughest residential and commercial jobs on lines up to 10" in diameter, this unit takes your modest jetting service to the next level. As a trailer-mounted model, it carries its own water supply for ample water flow. Plus, the electric hose reel supports wireless remote control capabilities.

Standard unit color is Safety yellow or white -Customer Choice. Can be custom painted to match almost any color for an additional charge.





3510-EStandard Components

200' of 3/8" thermoplastic sewer hose Hose Reel capacity - 350' of 3/8" hose (3510-E not compatible w/root cutter)

Standard Components

350 Gallon Polyethylene Tank

Plate mounted with sump and side baffles Crowned top & side stabilizers for added strength

Sufficient water supply for necessary water flow.

Cat Walk Fenders

Electric Reel

Oversized high-torque motor for rewind. Positive forward/reverse pressure switch. Variable-speed control.

Triplex Pump

Standard 10 GPM @ 2,500 psi

Honda Engine

Twin-cylinder/20hp
Electric start with charging system

High-Impact Thermoplastic Sewer Hose

Easy to clean off (leaves no bacteria-causing residue).

Maintains stiffness and is abrasion resistant.

Trailer

The Trailer Jetter is rated to carry a full tank of water to the job \dots

- 3" channel frame
- A-frame hitch
- 2" ball hitch
- 6,000 lb. DOT-rated axle
- ST-225 x 75R15 tires,Load Range D, 8 ply
- · Electric brakes

Other Standard Components

Two nozzles: one penetrator & one flusher Toolbox

PVC tank drain valve with stainless steel strainer Air purge system

20' Leader hose contrasting color

(check all that apply)
18" tall (PN OBJ-714
PN OB00016A)
PN OB00018A)
look (PN 015-438)
- Magnetic Mount (PN RL650A)
gnetic Mount (PN SL650A)
S" (PN J-2204)
S" (PN J-2203)
2" (PN J-2204)
pare (PN J-700-9)
Guide (PN J-2401)
w/Hose (PN 15007-B)
netic Mount (PN OBJ-500R)
Date:

Toll Free Phone: (800)638-1901 sales@obrienmfg.com

Fax: (888)638-1902 www.obrienmfg.com

Signature: _