

www.obrienmfg.com toll-free phone: 800-638-1901

# **10-F** Tailer Jetter



# **The Big Machine** at Home or the Office

For the toughest residential and commercial jobs on lines up to 10" in diameter, this unit takes your modest jetting service to the next level. As a trailer-mounted model, it carries its own water supply for ample water flow. This, combined with its horsepower, facilitates the use of a root cutter accessory. Plus, the electric hose reel supports wireless remote control capabilities.

Standard unit color is Safety yellow or white -Customer Choice. Can be custom painted to match almost any color for an additional charge.

Specifications subject to change without notice. Freight FOB Marietta, OH

Available Options (Check all that apply)100' 1/2" 4000PSI Extra Hose on Main Reel (PN OBJ-100-12AH)
Cone Holder Only (PN OBJ-137)
Garden Hose Reel 1/2" - 50' Reel (PN OBJ-123000L)
Garden Hose Reel Man.100' Cox (PN OBJ-293)
Hand Held Tethered Remote (OBJ-9061)
IntelACount® (OBJ-2430H)
Aux Hose Reel w/Long Handle, Foot Control Pedal (PN OBJ-40027A)
Level Wind Guide w/Counter (PN OBJ-2430A)
Low Water shutdown (PN OBJ-2424)
Custom Paint (Paint Code Required)
Pintle Hitch (PN OBJ-4001PW)
Pulsator P420 (PN 22735)
Recirculation System (PN OBJ-1/2"RECIRC)
Rotating Beacon-Fixed (PN OBJ-241B)
Wireless Remote (PN OBJ-102)





# 3510-FC

# **Standard Components**

300' of 1/2" thermoplastic sewer hose Hose reel capacity is 420' of 1/2" Compatible with OBJ-1468 root cutter

## **Standard Components**

## 350 Gallon Polyethylene Tank

Plate mounted with sump and side baffles Crowned top & side stabilizers for added strength

Sufficient water supply for necessary water flow.

#### **Electric Reel**

Oversized high-torque motor for rewind. Positive forward/reverse pressure switch. Variable-speed control.

#### **Triplex Pump**

Standard 10 GPM @ 2,500 psi

### **Honda Engine**

Twin-cylinder/20hp

Electric start with charging system

#### **CatWalk Fenders**

Note: Battery not included.

### **Available Accessories**

<b>High-Impact</b>	Thermop	lastic S	Sewer	Hose

Easy to clean off (leaves no bacteria-causing residue).

Maintains stiffness and is abrasion resistant.

#### **Trailer**

The Trailer Jetter is rated to carry a full tank of water to the job . . .

- 3" channel frame
- A-frame hitch
- 2" ball hitch
- 6,000 lb. DOT-rated axle
- ST-225 x 75R15 tires
- Electric brakes

## **Other Standard Components**

Two nozzles: one penetrator & one flusher

PVC tank drain valve with stainless steel strainer

Air purge system

20' Leader hose contrasting color

(check all that apply) Level wind guide Artillery Nozzle Kit (PN 121025AR) Aux Hose Reel w/ wheels, long handle, and 150' x 3/8" hose (PN OB40027A) Cavalry Nozzle Kit (PN 121025CA) \_Cone Safety Red 18" Tall (PN OBJ-714) \_Fill Hose 25' (PN J-2439) Foot Control for Hose Reel Wind/UnWind (PN OBJ-20027C) Foot Control Valve (PN OBJ-20027A) Tiger Tail - 2" x 36" (PN J-2204) Grit Catcher - 6" (PN OB00016A) \_Tiger Tail - 3" x 36" (PN J-2203) Grit Catcher - 8" (PN OB00018A) \_Tiger Tail - 3"x 42" (PN J-2205) Infantry Nozzle Kit (PN 121025IN) Tire & Rim 15" Spare (PN J-700-9) Lateral Cleaning Kit 150' (PN J-2432) \_Upstream Pulley Guide (PN J-2401) Lateral Cleaning Kit 200' (PN J-2432-2) Washdown Gun w/Hose (PN 15007-B) Manhole Cover Hook (PN 015-438) Work Light- Magnetic Mount (PN OBJ-500R) Nozzle Extension - Finned 1/2" (PN J-40-7) Nozzle Extension - Non Finned 1/2" (PN J-40-3) Root Cutter Kit (PN OBJ-1468) Rotating Beacon - Magnetic Mount (PN RL650A) Strobe Light - Magnetic Mount (PN SL650)

Printed Name: Date:

> Toll Free Phone: (800)638-1901 Fax: (888)638-1902

> sales@obrienmfg.com www.obrienmfg.com

Signature: