





QUALITY = PERFORMANCE = PUBLIC SAFETY
VALUE = CUSTOMER SUPPORT

800-879-7933 www.schwarze.com

## SuperVac Vortex<sup>™</sup>

4.5 Cubic Yard Parking Lot Sweeper

**Custom Made-to-Order** Hvdraulic Hoses: Reduces the opportunity for contamination in Hydraulic System

No butt connectors, all soldered connections: Increased uptime with the use of severe duty wiring that eliminates shorts caused by poor connections.

> Welded Hopper Assembly: No leaks

# **PERFORMANCE**

Leaf Bleeder: Allows you to exhaust up to 80% of the air. This gives the ability to better adjust the airflow based on varying material conditions

> Hardox Steel Fan: Eliminates the need for a fan coating, and creates a longer Life Expectancy equates to reduced cost of ownership

> > Bolt In, Replaceable Fan Liner: Ease of Maintenance (Reduced Cost of Ownership)

Noise Level: Reduce operator stress, and increased ability to operate in noise sensitive areas

AMERICAN BUILT -AMERICAN MADE



**Hydraulic Dumping Hopper:** 

Eliminates the requirement for manual unloading of debris for operator safety

> Backup Alarm: Variable output backup alarm adjust automatically above the surrounding noise levels

### VALUE


**Hydraulic Test** Ports: Reduces troubleshooting time

Slide-out Screens: Provides Easy Removal of Screen for Cleaning

#### Sweeps-In-Reverse<sup>™</sup>:

Increased productivity by operating in reverse without damaging sweeping head





Also Available from Schwarze Industries, Inc:

















Whisper Wheel<sup>™</sup> Fan System



Parts Availability: Schwarze original equipment parts are available when you need them.



Trusted Dealers: Trusted dealers will support your before and after-purchase needs.



**Empowered and Responsive:** Schwarze People are valued for their commitment to our future.



Schwarze Products: Engineered for enhanced sweeping performance and low ownership cost.


### CUSTOMER SUPPORT



Warranty Support: Schwarze people are on duty to support you and your equipment.

Schwarze regenerative air sweepers are guaranteed to be free from defects due to faulty materials and/or workmanship for a period of 12 months, or 1200 hours. Liability is limited to replacement of defective parts at factory or authorized dealer. The standard warranties of the chassis and sweeper engine manufacturer shall apply.

#### The People You Know. The Products You Trust.





Model shown with optional equipment. Design and specifications subject to change without notice. Specifications may vary depending on chassis type.

		woder snown with optional equipmen	t. Design and specifications subject to cha	ange without notice. Specifications may va	ny depending on chassis type.
Weights and Dimensions		Blower Fan		Safety	
Total Empty Weight Overall Width Overall Length Overall Height Wheelbase Turning Radius Sweeping Width (Head Only) Sweeping Width (Single Broom Dumping Height	9,940 lbs (4509kg) 85" (2159mm) 221" (5613mm) 99" (2515mm) 109" (2769mm) 15'9" (4801mm) 82" (2083mm) ) 98" (2489mm) 69" (1753mm)	Design  Type  Drive  Construction  Balance  Housing Liner  Vacuum Enhancher	Whisper Wheel <sup>sM</sup> 26" Blade Radial Pressure Backward Incline Variable Direct Hydraulic Motor AR Hardox Steel Within 1.5 grams Bolt-In Corded Rubber	Warning Labels Hopper Safety Props LED Tool Storage Lights Built-in Rear Strobe Lights HD Rear Bumper with Steps Factory Certified Training LED Lighting Chassis	
Gutter Broom			Adjustable	Make	Isuzu
Type Diameter Drive Speed Segments  Debris Hopper  Capacity Construction  Dumping Dump Door Dump Door Dimensions  Inspection Doors  Dumping Height Controls Dump Angle Dust Separator Intake Tube	Vertical Steel Digger 26" (660mm) Hydraulic Torque Motor Variable Bolt-On Disposable  4.5 Cubic Yards (3.4m3) Welded Steel Stainless (opt) Hydraulic to Rear Top Opening Hydraulic 63" X 54.25" (1600mm x 1378mm) (2) 12.25" X 26" (311mm) X 660mm) 69" (1753mm) In-Cab 88 degrees Centrifugal Bolt-In Replaceable	Type Suspension Construction Width Suction Diameter Blast Diameter Direction Skids Flap Replacement Litter Flaps  Hydraulic System Capacity Drive Filtration Warranty	Blast and Suction (right to left) (4) Adjustable Spring Single Piece Steel w/ Channel Guard 82" (2083mm) 10" (254mm) Forward and Reverse High Visibility Carbide Quick Change No Tools Open Channel Front, Curved Rear	Model Type GVWR  Engine  Transmission Frame  Tires  Wheels Brakes  Steering  Electrical Alternator Batteries  Auxiliary Engine	NPR Gas Cab-forward 12,000LB / 14,500LB (5152kg / 9298.64kg) GM 6.0 Liter gas engine 6-speed automatic 44,000 psi (3093.45kg/cm2), 7.2 in2 SM (6) 19.5" tires on 14,500 GVWR Steel Disc, 6-hole Vacuum/Hydraulic with 4 channel ABS Integral Power Tilt and Telescoping 12 volt 110 amp Dual 750 CCA
De inst	Steel	Dust Control	US L B	Make Model	Kohler ECH740
Paint Hopper Underbody Hopper Screen	Dupont Imron 5000 Textured Black Urethane	Type Pump Capacity Construction Filtration Controls	High Pressure / Low Volume 12 Volt Diaphragm 93 Gallons Polyethylene 100 Mesh In-Cab with exterior	gm  Limited Warranty  12 month / 1200 hour, 60 month hydraulic system; call for	
Design Area	1 Piece Full Width Expanded Metal 2211 in <sup>2</sup> inches (1.42m2)	Nozzles	flow control Hopper, Sweeping Head and Gutter Broom	NOTE: Specifications are sub notice	ject to change without
Removal	Slide-out design	Tool Storage			
Controls		Location Capacity	2 at Rear 17.25 cu ft (488.471)		
Switches Labeling	Heavy Duty Rocker Type International Symbols	Latches Crosslink Channels	Lockable Steel For Rake and Shovel Storage		









